



Characteristics

Media: 100% Synthetic Polypropylene Microfiber

Pockets: Ultrasonically Welded Seams & Edges

Pocket Flutes: Ultrasonically Welded Support Spacers

Header: Electro-Galvanized Metal Header and "J" Style Media Retainers

Air Flow Bag 50%-8 Pocket

Model Number	Width "A"	Height "B"	Depth "C"	Number of Pockets	Air Flow Capacity (cfm)	Initial Resistance ("w.g.)
AFB850S-4430	23-3/8"	23-3/8"	30"	8	2000	.19
AFB850S-4426	23-3/8"	23-3/8"	26"	8	1500	.18
AFB850S-4422	23-3/8"	23-3/8"	22"	8	1500	.19
AFB850S-4415	23-3/8"	23-3/8"	15"	8	1000	.19
AFB650S-0430	19-3/8"	23-3/8"	30"	6	1500	.19
AFB650S-0426	19-3/8"	23-3/8"	26"	6	1125	.18
AFB650S-0422	19-3/8"	23-3/8"	22"	6	1125	.19
AFB650S-0415	19-3/8"	23-3/8"	15"	6	750	.19
AFB450S-2430	11-3/8"	23-3/8"	30"	4	1000	.19
AFB450S-2426	11-3/8"	23-3/8"	26"	4	750	.18
AFB450S-2422	11-3/8"	23-3/8"	22"	4	750	.19
AFB450S-2415	11-3/8"	23-3/8"	15"	4	500	.19

Notes:

Standard: UL 900, Class 2

Available with the following gasketing options:

- GU - Gasket Upstream
- GD - Gasket Downstream
- GS - Gasket Sides

Other Options:

- C - Cambridge Header
- 1 - UL 900, Class 1

An example of the part number with options is: AFB850S-4430GU



100 Oak Tree Drive
Selma, NC 27576

Phone: 919-975-0240
Fax: 919-975-0250

Air Flow Bag 50%, MERV 10
8 Pocket

Date 10/29/02

Part Number

Revision

Approved

AFB850S

A