



Characteristics

Media: 100% Synthetic Polypropylene Microfiber  
 Pockets: Ultrasonically Welded Seams & Edges  
 Pocket Flutes: Ultrasonically Welded Support Spacers  
 Header: Electro-Galvanized Metal Header and "J" Style Media Retainers

Air Flow Bag 85%-8 Pocket						
Model Number	Width "A"	Height "B"	Depth "C"	Number of Pockets	Air Flow Capacity (cfm)	Initial Resistance ("w.g.)
AFB885S-4430	23-3/8"	23-3/8"	30"	8	2000	.18
AFB885S-4426	23-3/8"	23-3/8"	26"	8	1500	.26
AFB885S-4422	23-3/8"	23-3/8"	22"	8	1500	.12
AFB885S-4415	23-3/8"	23-3/8"	15"	8	1000	.28
AFB685S-0430	19-3/8"	23-3/8"	30"	6	1500	.28
AFB685S-0426	19-3/8"	23-3/8"	26"	6	1125	.26
AFB685S-0422	19-3/8"	23-3/8"	22"	6	1125	.28
AFB685S-0415	19-3/8"	23-3/8"	15"	6	750	.28
AFB485S-2430	11-3/8"	23-3/8"	30"	4	1000	.28
AFB485S-2426	11-3/8"	23-3/8"	26"	4	750	.26
AFB485S-2422	11-3/8"	23-3/8"	22"	4	750	.28
AFB485S-2415	11-3/8"	23-3/8"	15"	4	500	.28

Notes:

Standard: UL 900, Class 2

Available with the following gasketing options:

- GU - Gasket Upstream
- GD - Gasket Downstream
- GS - Gasket Sides

Other Options:

- C - Cambridge Header
- 1 - UL 900, Class 1

An example of the part number with options is: AFB885S-4430GU



100 Oak Tree Drive  
 Selma, NC 27576

Phone: 919-975-0240  
 Fax: 919-975-0250

Air Flow Bag 85%, MERV 13  
 8 Pocket

Date	11/02/02	Part Number	AFB885S	Revision	B
Approved					