



Characteristics

Media: 100% Synthetic Polypropylene Microfiber

Pockets: Ultrasonically Welded Seams & Edges

Pocket Flutes: Ultrasonically Welded Support Spacers

Header: Electro-Galvanized Metal Header and "J" Style Media Retainers

Air Flow Bag 95% - 12 Pocket						
Model Number	Width "A"	Height "B"	Depth "C"	Number of Pockets	Air Flow Capacity (cfm)	Initial Resistance ("w.g.)
AFB1295S-4415	23-3/8"	23-3/8"	15"	12	1500	.35
AFB1095S-0415	19-3/8"	23-3/8"	15"	10	1250	.35
AFB1095S-0015	19-3/8"	19-3/8"	15"	10	1000	.35
AFB695S-2415	11-3/8"	23-3/8"	15"	6	750	.35

Notes:

Standard: UL 900, Class 2

Available with the following gasketing options:

- GU - Gasket Upstream
- GD - Gasket Downstream
- GS - Gasket Sides

Other Options:

- C - Cambridge Header
- 1 - UL 900, Class 1

An example of the part number with options is: AFB1295S-4415GU



airflow products company  
**AIRFLOW**  
INCORPORATED

100 Oak Tree Drive  
Selma, NC 27576

Phone: 919-975-0240  
Fax: 919-975-0250

**Air Flow Bag 95%, MERV 14,  
12 Pocket**

<small>Date</small>	11/02/02	<small>Part Number</small>	<b>AFB1295S</b>	<small>Revision</small>	<b>A</b>
<small>Approved</small>					