



Characteristics

Frame: 100% polypropylene plastic board.
 Media: 100% polypropylene fibers, water and bacteria resistant.
 Media is spaced and supported with beads of polypropylene polymer.
 Media bonded to frame using polypropylene adhesive.

Air Flow MiniPleat - 2" Nominal Depth, 90%-95%, MERV 14			
Model Number	Width "A"	Height "B"	Depth "C"
AFMP95-24242	23-3/8"	23-3/8"	1-7/8"
AFMP95-20252	19-1/2"	24-1/2"	1-7/8"
AFMP95-20242	19-1/2"	23-3/8"	1-7/8"
AFMP95-20202	19-1/2"	19-1/2"	1-7/8"
AFMP95-16252	15-1/2"	24-1/2"	1-7/8"
AFMP95-16202	15-1/2"	19-1/2"	1-7/8"
AFMP95-12242	11-3/8"	23-3/8"	1-7/8"

Notes:

UL 900, Class 2
 90%-95% per ASHRAE 52.1
 MERV 14 per ASHRAE 52.2

Initial Resistance:
 @ 500 FPM: 0.81" w.g.
 @ 300 FPM: 0.42" w.g.



100 Oak Tree Drive
 Selma, NC 27576

Phone: 919-975-0240
 Fax: 919-975-0250

Air Flow MiniPleat, 2" Nominal Depth
 90%-95% MERV 14

Date	11/03/02	Part Number	AFMP95-2	Revision	A
Approved					