



Characteristics

Frame: 100% polypropylene plastic board
 Media: 100% polypropylene fibers, water and bacteria resistant
 Media is spaced and supported with beads of polypropylene polymer.
 Media bonded to frame using polypropylene adhesive.

Air Flow MiniPleat - 4" Nominal Depth, 60%-65%, MERV 11-12			
Model Number	Width "A"	Height "B"	Depth "C"
AFMP65-24244	23-3/8"	23-3/8"	3-3/4"
AFMP65-20254	19-1/2"	24-1/2"	3-3/4"
AFMP65-20244	19-1/2"	23-3/8"	3-3/4"
AFMP65-20204	19-1/2"	19-1/2"	3-3/4"
AFMP65-16254	15-1/2"	24-1/2"	3-3/4"
AFMP65-16204	15-1/2"	19-1/2"	3-3/4"
AFMP65-12244	11-3/8"	23-3/8"	3-3/4"

Notes:

UL 900, Class 2
 60%-65% per ASHRAE 52.1
 MERV 11-12 per ASHRAE 52.2
 Initial Resistance:
 @ 500 FPM: 0.36" w.g.
 @ 300 FPM: 0.18" w.g.



100 Oak Tree Drive
 Selma, NC 27576

Phone: 919-975-0240
 Fax: 919-975-0250

Air Flow MiniPleat, 4" Nominal Depth
 60%-65% MERV 11-12

Date	11/04/02	Part Number	AFMP65-4	Revision	A
Approved					