



Characteristics

Frame: 100% polypropylene plastic board  
 Media: 100% polypropylene fibers, water and bacteria resistant  
 Media is spaced and supported with beads of polypropylene polymer.  
 Media bonded to frame using polypropylene adhesive.

Air Flow MiniPleat - 4" Nominal Depth, 80%-85%, MERV 13			
Model Number	Width "A"	Height "B"	Depth "C"
AFMP85-24244	23-3/8"	23-3/8"	3-3/4"
AFMP85-20254	19-1/2"	24-1/2"	3-3/4"
AFMP85-20244	19-1/2"	23-3/8"	3-3/4"
AFMP85-20204	19-1/2"	19-1/2"	3-3/4"
AFMP85-16254	15-1/2"	24-1/2"	3-3/4"
AFMP85-16204	15-1/2"	19-1/2"	3-3/4"
AFMP85-12244	11-3/8"	23-3/8"	3-3/4"

Notes:

UL 900, Class 2  
 80%-85% per ASHRAE 52.1  
 MERV 13 per ASHRAE 52.2  
 Initial Resistance:  
 @ 500 FPM: 0.45" w.g.  
 @ 300 FPM: 0.24" w.g.



100 Oak Tree Drive  
 Selma, NC 27576

Phone: 919-975-0240  
 Fax: 919-975-0250

Air Flow MiniPleat, 4" Nominal Depth  
 80%-85% MERV 13

Date	11/04/02	Part Number	AFMP85-4	Revision	A
Approved					