



Characteristics

Frame: 100% polypropylene plastic board
 Media: 100% polypropylene fibers, water and bacteria resistant
 Media is spaced and supported with beads of polypropylene polymer.
 Media bonded to frame using polypropylene adhesive.

Air Flow MiniPleat - 4" Nominal Depth, 90%-95%, MERV 14			
Model Number	Width "A"	Height "B"	Depth "C"
AFMP95-24244	23-3/8"	23-3/8"	3-3/4"
AFMP95-20254	19-1/2"	24-1/2"	3-3/4"
AFMP95-20244	19-1/2"	23-3/8"	3-3/4"
AFMP95-20204	19-1/2"	19-1/2"	3-3/4"
AFMP95-16254	15-1/2"	24-1/2"	3-3/4"
AFMP95-16204	15-1/2"	19-1/2"	3-3/4"
AFMP95-12244	11-3/8"	23-3/8"	3-3/4"

Notes:

UL 900, Class 2
 90%-95% per ASHRAE 52.1
 MERV 14 per ASHRAE 52.2

Initial Resistance:
 @ 500 FPM: 0.62" w.g.
 @ 300 FPM: 0.32" w.g.



100 Oak Tree Drive
 Selma, NC 27576

Phone: 919-975-0240
 Fax: 919-975-0250

Air Flow MiniPleat, 4" Nominal Depth
 90%-95% MERV 14

Date 11/04/02

Part Number

Revision

Approved

AFMP95-4

A