



Characteristics

Frame: 100% polypropylene plastic board
 Media: 100% polypropylene fibers, water and bacteria resistant
 Media is spaced and supported with beads of polypropylene polymer.
 Media bonded to frame using polypropylene adhesive.

Air Flow MiniPleat - 4" Nominal Depth, 98%, MERV 15			
Model Number	Width "A"	Height "B"	Depth "C"
AFMP98-24244	23-3/8"	23-3/8"	3-3/4"
AFMP98-20254	19-1/2"	24-1/2"	3-3/4"
AFMP98-20244	19-1/2"	23-3/8"	3-3/4"
AFMP98-20204	19-1/2"	19-1/2"	3-3/4"
AFMP98-16254	15-1/2"	24-1/2"	3-3/4"
AFMP98-16204	15-1/2"	19-1/2"	3-3/4"
AFMP98-12244	11-3/8"	23-3/8"	3-3/4"

Notes:

UL 900, Class 2
 98% per ASHRAE 52.1
 MERV 15 per ASHRAE 52.2
 Initial Resistance:
 @ 500 FPM: 0.71" w.g.
 @ 300 FPM: 0.42" w.g.



100 Oak Tree Drive
 Selma, NC 27576

Phone: 919-975-0240
 Fax: 919-975-0250

Air Flow MiniPleat, 4" Nominal Depth
 98% MERV 15

Date	11/04/02	Part Number	AFMP98-4	Revision	A
Approved					