



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.  
 Media: 100% synthetic fibers, water and bacteria resistant.  
 Media bonded to frame using water resistant adhesive.  
 Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, Standard Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP2000-5502	24-1/2"	24-1/2"	1-3/4"
AFP2000-4402	23-3/8"	23-3/8"	1-3/4"
AFP2000-0502	19-1/2"	24-1/2"	1-3/4"
AFP2000-0402	19-1/2"	23-3/8"	1-3/4"
AFP2000-0002	19-1/2"	19-1/2"	1-3/4"
AFP2000-8502	17-3/8"	24-1/2"	1-3/4"
AFP2000-8402	17-3/8"	23-3/8"	1-3/4"
AFP2000-6502	15-1/2"	24-1/2"	1-3/4"
AFP2000-6002	15-1/2"	19-1/2"	1-3/4"
AFP2000-2402	11-3/8"	23-3/8"	1-3/4"
AFP2000-2002	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900, Class 2  
 25%-30% per ASHRAE 52.1  
 MERV 7-8 per ASHRAE 52.2  
 Initial Resistance:  
 @ 500 FPM: 0.26" w.g.  
 @ 300 FPM: 0.14" w.g.



100 Oak Tree Drive  
 Selma, NC 27576

Phone: 919-975-0240  
 Fax: 919-975-0250

Air Flow Pleat, 2" Nominal Depth  
 Standard Capacity, 25%-30%,  
 MERV 7- 8

Date 11/04/02	Part Number AFP2000-2	Revision A
Approved		