



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant, impregnated with granular carbon.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5502-C	24-1/2"	24-1/2"	1-3/4"
AFP3000-4402-C	23-3/8"	23-3/8"	1-3/4"
AFP3000-0502-C	19-1/2"	24-1/2"	1-3/4"
AFP3000-0402-C	19-1/2"	23-3/8"	1-3/4"
AFP3000-0002-C	19-1/2"	19-1/2"	1-3/4"
AFP3000-8502-C	17-3/8"	24-1/2"	1-3/4"
AFP3000-8402-C	17-3/8"	23-3/8"	1-3/4"
AFP3000-6502-C	15-1/2"	24-1/2"	1-3/4"
AFP3000-6002-C	15-1/2"	19-1/2"	1-3/4"
AFP3000-2402-C	11-3/8"	23-3/8"	1-3/4"
AFP3000-2002-C	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900, Class 2

25%-30% per ASHRAE 52.1

MERV 7-8 per ASHRAE 52.2

Initial Resistance:

@ 500 FPM: 0.26" w.g.

@ 300 FPM: 0.14" w.g.



100 Oak Tree Drive
Selma, North Carolina

Phone: 919-975-0240
Fax: 919-975-0250

Air Flow Pleat, 2" Nominal Depth
High Capacity, 25%-30%,
Carbon Impregnated

Date	3/14/03	Part Number	AFP3000-2-C	Revision
Approved				