



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 2" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5502	24-1/2"	24-1/2"	1-3/4"
AFP3000-4402	23-3/8"	23-3/8"	1-3/4"
AFP3000-0502	19-1/2"	24-1/2"	1-3/4"
AFP3000-0402	19-1/2"	23-3/8"	1-3/4"
AFP3000-0002	19-1/2"	19-1/2"	1-3/4"
AFP3000-8502	17-3/8"	24-1/2"	1-3/4"
AFP3000-8402	17-3/8"	23-3/8"	1-3/4"
AFP3000-6502	15-1/2"	24-1/2"	1-3/4"
AFP3000-6002	15-1/2"	19-1/2"	1-3/4"
AFP3000-2402	11-3/8"	23-3/8"	1-3/4"
AFP3000-2002	11-3/8"	19-1/2"	1-3/4"

Notes:

UL 900, Class 2

25%-30% per ASHRAE 52.1

MERV 7- 8 per ASHRAE 52.2

Initial Resistance:

@ 500 FPM: 0.26" w.g.

@ 300 FPM: 0.14" w.g.



100 Oak Tree Drive
Selma, NC 27576

Phone: 919-975-0240
Fax: 919-975-0250

Air Flow Pleat, 2" Nominal Depth
High Capacity, 25%-30%,
MERV 7-8

Date	11/04/02	Part Number	AFP3000-2	Revision	A
Approved					