



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.

Media: 100% synthetic fibers, water and bacteria resistant.

Media bonded to frame using water resistant adhesive.

Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, Economy Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP1000-5504	24-1/2"	24-1/2"	3-3/4"
AFP1000-4404	23-3/8"	23-3/8"	3-3/4"
AFP1000-0504	19-1/2"	24-1/2"	3-3/4"
AFP1000-0404	19-1/2"	23-3/8"	3-3/4"
AFP1000-0004	19-1/2"	19-1/2"	3-3/4"
AFP1000-8504	17-3/8"	24-1/2"	3-3/4"
AFP1000-8404	17-3/8"	23-3/8"	3-3/4"
AFP1000-6504	15-1/2"	24-1/2"	3-3/4"
AFP1000-6004	15-1/2"	19-1/2"	3-3/4"
AFP1000-2404	11-3/8"	23-3/8"	3-3/4"
AFP1000-2004	11-3/8"	19-1/2"	3-3/4"

Notes:

UL 900, Class 2

25%-30% per ASHRAE 52.1

MERV 7-8 per ASHRAE 52.2

Initial Resistance:

@ 500 FPM: 0.28" w.g.

@ 300 FPM: 0.24" w.g.



100 Oak Tree Drive
Selma, NC 27576

Phone: 919-975-0240
Fax: 919-975-0250

Air Flow Pleat, 4" Nominal Depth
Economy Capacity, 25%-30%,
MERV 7-8

Date	11/04/02	Part Number	AFP1000-4	Revision	A
Approved					