



Characteristics

Frame: 26 point high wet strength clay-coated kraft board.
 Media: 100% synthetic fibers, water and bacteria resistant.
 Media bonded to frame using water resistant adhesive.
 Media bonded to expanded metal support grid using water resistant adhesive.

Air Flow Pleat - 4" Nominal Depth, High Capacity			
Model Number	Width "A"	Height "B"	Depth "C"
AFP3000-5504	24-1/2"	24-1/2"	3-3/4"
AFP3000-4404	23-3/8"	23-3/8"	3-3/4"
AFP3000-0504	19-1/2"	24-1/2"	3-3/4"
AFP3000-0404	19-1/2"	23-3/8"	3-3/4"
AFP3000-0004	19-1/2"	19-1/2"	3-3/4"
AFP3000-8504	17-3/8"	24-1/2"	3-3/4"
AFP3000-8404	17-3/8"	23-3/8"	3-3/4"
AFP3000-6504	15-1/2"	24-1/2"	3-3/4"
AFP3000-6004	15-1/2"	19-1/2"	3-3/4"
AFP3000-2404	11-3/8"	23-3/8"	3-3/4"
AFP3000-2004	11-3/8"	19-1/2"	3-3/4"

Notes:

UL 900, Class 2
 25%-30% per ASHRAE 52.1
 MERV 7-8 per ASHRAE 52.2
 Initial Resistance:
 @ 500 FPM: 0.18" w.g.
 @ 300 FPM: 0.12" w.g.



100 Oak Tree Drive
 Selma, NC 27576

Phone: 919-975-0240
 Fax: 919-975-0250

Air Flow Pleat, 4" Nominal Depth
 High Capacity, 25%-30%,
 MERV 7-8

Date	11/04/02	Part Number	AFP3000-4	Revision	A
Approved					